

CE

HIRE

ONFRS

SERVIC

POSITI

Precision and performance from every angle



BODE MEDIUM DUTY COLUMN PRECISION AND PERFORMANCE



Model 3/TRMB 4 m x 5 m Tracked unit with rotating column.

Model 3/TRMB 5 m x 4 m Set-up for seamless pipe welding using submerged arc welding unit.





Model 3/TRMB Utilised as shown in stainless steel container welding role. Container carried on Bode SAR 1200 Rotators. Remote control master station.

& BOOM MANIPULATORS FROM EVERY ANGLE

Model		Min. Height	Max. Height	Overall Height	Boom reach	Boom Travel speed	Max. Loa
		under Boom (mm)	under Boom (mm)	(mm)	(mm)	(mm/min.)	(kg)
0.001.00							
2/RMB		550	2000	2400	2000	100-2000	140
2/RMB		550	2000	2400	2500	100-2000	120
2/RMB		550	2500	2900	2000	100-2000	140
2/RMB	2.5x2.5	550	2500	2900	2500	100-2000	120
2/RMB(HD)	2x2	575	2000	2500	2000	100-2000	215
2/RMB(HD)	2x2.5	575	2000	2500	2500	100-2000	190
2/RMB(HD)	2.5x2	575	2500	3000	2000	100-2000	215
2/RMB(HD)	2.5x2.5	575	2500	3000	2500	100-2000	190
2/RMB(HD)	3x2	575	3000	3500	2000	100-2000	215
2/RMB(HD)	3x2.5	575	3000	3500	2500	100-2000	190
2/RMB(HD)	3x3	575	3000	3500	3000	100-2000	170
2/RMB(HD)	3x3.5	575	3000	3500	3500	100-2000	150
2/RMB(HD)	3x4	575	3000	3500	4000	100-2000	125
2/RMB(HD)	3.5x2	575	3500	4000	2000	100-2000	215
2/RMB(HD)		575	3500	4000	2500	100-2000	190
2/RMB(HD)		575	3500	4000	3000	100-2000	170
2/RMB(HD)		575	3500	4000	3500	100-2000	150
2/RMB(HD)		575	3500	4000	4000	100-2000	125
2/RMB(HD)	4~2	575	4000	4600	0000	400.0000	045
2/RMB(HD)		575		4500	2000	100-2000	215
2/RMB(HD)		575	4000	4500	2500	100-2000	190
2/RMB(HD)		575	4000	4500	3000	100-2000	170
2/RMB(HD)		575	4000	4500 4500	3500	100-2000	150 125
3/RMB		680	3000	4190	2500	100-2000	430
3/RMB		680	3000	4190	3000	100-2000	370
3/RMB		680	3000	4190	3500	100-2000	310
3/RMB	3x4	680	3000	4190	4000	100-2000	250
3/RMB	3.5x2.5	680	3500	4690	2500	100-2000	430
3/RMB	3.5x3	680	3500	4690	3000	100-2000	370
3/RMB	3.5x3.5	680	3500	4690	3500	100-2000	310
3/RMB	3.5x4	680	3500	4690	4000	100-2000	250
3/RMB	4x2.5	680	4000	5190	2500	100-2000	430
3/RMB	4x3	680	4000	5190	3000	100-2000	370
3/RMB	4x3.5	680	4000	5190	3500	100-2000	310
3/RMB	4x4	680	4000	5190	4000	100-2000	250
3/RMB	4.5x2.5	680	4500	5690	2500	100-2000	430
3/RMB		680	4500	5690	3000	100-2000	370
	4.5x3.5	680	4500	5690	3500	100-2000	310
3/RMB		680	4500	5690	4000	100-2000	250
	4.5x4.5	680	4500	5690	4500	100-2000	190
3/RMB	5x2.5	680	5000	6190	2500	100-2000	430
3/RMB		680	5000	6190	3000		
3/RMB		680	5000	· · · · · · · · · · · · · · · · · · ·		100-2000	370
3/RMB		680	5000	6190	3500	100-2000	310
	5x4.5	680	5000	6190 6190	4000	100-2000	250
		000	10000	. 01281	MC30.8.1	100-2000	230



YOU'LL NOTICE THE DIFFERENCE WITH BODE

同時書

Globally the Bode range of Column & Boom Manipulators stands out not only for innovation in design and quality of manufacture, but also for reliability and robustness.

 360° column rotation with manual locking at any position.

SERVICE

HIRE



- Free standing or variable speed travelling carriage.
- Optional fittings, including welding heads, available.

Whatever your need Bode will have the answer. Just talk to us, and remember, Bode also makes other ranges of Column & Boom Manipulators from portable to ultra heavy duty models.




F. Bode & Sons Limited

Unit No 1 Stubbins Lane Claughton-On-Brock Preston, Lancs England PR3 0QH

Tel.: +44 (0) 1995 643 210 Fax: +44 (0) 1995 643 211 E-mail - sales@bode.co.uk

Visit our web site - www.bode.co.uk



- Boom elevation through geared motor rack and pinion drive with elektro-magnetic brake.
- Elevation and traverse drive mounted on saddle providing for easy access servicing and maintenance.
- Machines fully counter-balanced by column internal weight, connected to the saddle by heavy duty wire rope. Anti-fall device offers full safety feature.
- Extra wide rollers and unique slideways ensure minimum deflection traversing.
- Innovative machined 'V' ways to column ensure that the boom saddle moves smoothly with no vibration. This reduces wear and tear.